

according to Regulation (EC) No 1907/2006

ARC 791(E) Part B

Revision date: 10.07.2023 Page 1 of 17

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

UFI: 0VAF-SNAQ-TH7K-921J

ARC 791(E) Part B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

ARC Polymer Composite. Repairs damage caused by impact, abrasion or erosion.

#### Uses advised against

No information available.

## 1.3. Details of the supplier of the safety data sheet

Company name: Chesterton International GmbH

Street: Am Lenzenfleck 23

Place: D-85737 Ismaning GERMANY

Telephone: +49 89 99 65 46 - 0 Telefax: +49 89 99 65 46 - 50

e-mail: eu-sds@chesterton.com

Contact person: eu-sds@chesterton.com Telephone: +49 89 99 65 46 - 0

e-mail: eu-sds@chesterton.com Internet: www.chesterton.com Responsible Department: eu-sds@chesterton.com

**1.4. Emergency telephone** +49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

number:

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

2-methylpentane-1,5-diamine

Signal word: Danger



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 2 of 17

#### Pictograms:





#### **Hazard statements**

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

## **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

## 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

## **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
100-51-6	benzyl alcohol			25-<50 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			25 - <50 %
	220-666-8	612-067-00-9	01-2119514687-32	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A; H302 H314 H318 H317			
15520-10-2	2-methylpentane-1,5-diamine			5 - <10 %
	239-556-6		01-2119976310-41	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1, Eye Dam. 1, STOT SE 3; H332 H312 H302 H314 H318 H335			

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 3 of 17

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
100-51-6	202-859-9	benzyl alcohol	25-<50 % %
	inhalation: LC5 LD50 = 1230 m	50 = 11 mg/l (vapours); inhalation: LC50 = > 4,178 mg/l (dusts or mists); oral: g/kg	
2855-13-2	220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine	25 - <50 %
	dermal: LD50 =	= > 2000 mg/kg; oral: ATE 1030 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100	
15520-10-2	239-556-6	2-methylpentane-1,5-diamine	5 - <10 %
	inhalation: LC50 = 11 mg/l (vapours); inhalation: LC50 = 4,9 mg/l (dusts or mists); dermal: LD50 = 1870 mg/kg; oral: LD50 = 1690 mg/kg		

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection!

Remove affected person from the danger area and lay down. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

## After inhalation

Remove casualty to fresh air and keep warm and at rest. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

### After contact with skin

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

## After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let 1 glass of water be drunken in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Causes severe skin burns and eye damage.
- Allergic reactions
- Gastrointestinal complaints

## 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 4 of 17

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

- Dry extinguishing powder.
- Carbon dioxide (CO2).
- Water spray jet

## Unsuitable extinguishing media

Full water jet

## 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

- Carbon monoxide
- Carbon dioxide (CO2).
- Nitrogen oxides (NOx)

## 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

## Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Safe handling: see section 7

Personal protection equipment: see section 8

Provide adequate ventilation as well as local exhaustion at critical locations.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Clean contaminated articles and floor according to the environmental legislation. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

#### For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 5 of 17

#### Advice on safe handling

Personal protection equipment: see section 8

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

When using do not eat, drink or smoke.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

#### Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Advice on general occupational hygiene

Avoid contact with skin, eyes and clothes. Use protective skin cream before handling the product. Remove contaminated, saturated clothing immediately. When using do not eat, drink, smoke, sniff. Wash hands and face before breaks and after work and take a shower if necessary.

#### Further information on handling

Wash hands before breaks and after work. Used working clothes should not be worn outside the work area. Street clothing should be stored separately from work clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container. Protect from direct sunlight.

#### Hints on joint storage

Keep away from:

- Food and feedingstuffs

## Further information on storage conditions

Keep away from:

- Frost
- Heat
- Humidity

#### 7.3. Specific end use(s)

No data available

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters



according to Regulation (EC) No 1907/2006

# ARC 791(E) Part B

Revision date: 10.07.2023 Page 6 of 17

#### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
100-51-6	benzyl alcohol			
Worker DNEL,	long-term	inhalation	systemic	22 mg/m³
Worker DNEL,	acute	inhalation	systemic	110 mg/m³
Worker DNEL,	long-term	dermal	systemic	8 mg/kg bw/day
Worker DNEL,	acute	dermal	systemic	40 mg/kg bw/day
Consumer DNI	EL, long-term	inhalation	systemic	5,4 mg/m³
Consumer DNI	EL, acute	inhalation	systemic	27 mg/m³
Consumer DNI	EL, long-term	dermal	systemic	4 mg/kg bw/day
Consumer DNI	EL, acute	dermal	systemic	20 mg/kg bw/day
Consumer DNI	EL, long-term	oral	systemic	4 mg/kg bw/day
Consumer DNI	EL, acute	oral	systemic	20 mg/kg bw/day
,				
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			
Worker DNEL,	long-term	inhalation	local	0,073 mg/m³
Consumer DNI	EL, acute	oral	systemic	0,3 mg/kg bw/day
Worker DNEL,	acute	inhalation	local	0,073 mg/m³
Consumer DNI	EL, long-term	oral	systemic	0,3 mg/kg bw/day
15520-10-2	2-methylpentane-1,5-diamine			
Worker DNEL,	acute	inhalation	local	0,5 mg/m³
Consumer DNI	EL, acute	inhalation	local	0,25 mg/m³
Worker DNEL, long-term		inhalation	local	0,25 mg/m³
Worker DNEL, long-term		dermal	systemic	1,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	0,125 mg/m³
Consumer DNI	EL, long-term	dermal	systemic	0,75 mg/kg bw/day
Consumer DNI	Consumer DNEL, long-term		systemic	0,25 mg/kg bw/day



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 7 of 17

#### **PNEC values**

CAS No	Substance	
Environmenta	al compartment	Value
100-51-6	benzyl alcohol	
Freshwater		1 mg/l
Freshwater (i	ntermittent releases)	2,3 mg/l
Marine water		0,1 mg/l
Freshwater s	ediment	5,27 mg/kg
Marine sedim	nent	0,527 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	39 mg/l
Soil		0,456 mg/kg
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	
Freshwater		0,06 mg/l
Freshwater (intermittent releases)		0,23 mg/l
Marine water		0,006 mg/l
Freshwater s	ediment	5,784 mg/kg
Marine sedim	nent	0,578 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	3,18 mg/l
Soil		1,121 mg/kg
15520-10-2	2-methylpentane-1,5-diamine	
Freshwater		0,93 mg/l
Freshwater (intermittent releases)		0,93 mg/l
Marine water		0,093 mg/l
Freshwater sediment		144,7 mg/kg
Marine sediment		14,5 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	29,1 mg/l
Soil		3,52 mg/kg

## 8.2. Exposure controls

## Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. If handled uncovered, arrangements with local exhaust ventilation have to be used.

## Individual protection measures, such as personal protective equipment

## Eye/face protection

Suitable eye protection: Eye glasses with side protection

spray application: Wear face protection.



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 8 of 17

#### Hand protection

Tested protective gloves must be worn: EN ISO 374 NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material >= 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))

Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))

Observe the wear time limits as specified by the manufacturer.

#### Skin protection

Protective clothing

spray application: Chemical protection clothing

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

spray application: Use appropriate respiratory protection.

#### Thermal hazards

No data available

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: transparent
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range: Flammability

No data available Solid/liquid: Lower explosion limits: No data available Upper explosion limits: No data available Flash point: > 83 °C Auto-ignition temperature: > 350 °C Decomposition temperature: No data available pH-Value (at 23 °C): ~ 12,1 Water solubility: No data available

Solubility in other solvents

No information available.



according to Regulation (EC) No 1907/2006

ARC 791(E) Part B

Revision date: 10.07.2023 Page 9 of 17

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 23 °C):

Relative vapour density:

No data available

~ 1,0 g/cm³

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No information available. Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No information available.

Other safety characteristics

Evaporation rate:

Viscosity / dynamic:

No data available

~ 300 mPa·s

(at 23 °C)

**Further Information** 

No information available.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

## 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

## 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

## 10.4. Conditions to avoid

No data available

## 10.5. Incompatible materials

No data available

#### 10.6. Hazardous decomposition products

No data available

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Harmful if swallowed.

Harmful if inhaled.



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 10 of 17

#### **ATEmix** calculated

ATE (oral) 1152,2 mg/kg; ATE (dermal) 23375,0 mg/kg; ATE (inhalation vapour) 20,37 mg/l; ATE (inhalation dust/mist) 2,688 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
100-51-6	benzyl alcohol					
	oral	LD50 mg/kg	1230	Mouse	Cosmet. Toxicol. 11, 1011-1013 (1973) (1	OECD Guideline 401
	inhalation vapour	LC50	11 mg/l			
	inhalation (4 h) dust/mist	LC50 mg/l	> 4,178	Rat	ECHA	OECD 403
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine					
	oral	ATE 103	0 mg/kg			
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2010)	OECD Guideline 402
15520-10-2	2-methylpentane-1,5-diamine					
	oral	LD50 mg/kg	1690	Rat	Study report (1984)	OECD Guideline 401
	dermal	LD50 mg/kg	1870	Rat	Study report (1978)	OECD Guideline 402
	inhalation vapour	LC50	11 mg/l			
	inhalation (1 h) dust/mist	LC50	4,9 mg/l			

#### Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

## Sensitising effects

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## **Practical experience**

Respiratory or skin sensitisation / Irritation to respiratory tract: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### 11.2. Information on other hazards



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 11 of 17

## **Endocrine disrupting properties**

No data available

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

# ARC 791(E) Part B

Revision date: 10.07.2023 Page 12 of 17

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
100-51-6	benzyl alcohol						
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Oryzias latipes	Review article or handbook (2009)	OECD Guideline 203
	Acute algae toxicity	ErC50	770 mg/l	72 h	Raphidocelis subcapitata	Review article or handbook (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50	230 mg/l	48 h	Daphnia magna	Review article or handbook (2009)	OECD Guideline 202
	Fish toxicity	NOEC mg/l	48,897	30 d	Fish species	http://epa.gov/oppt /exposure/pubs/ep isui	other: QSAR
	Algae toxicity	NOEC	51 mg/l	3 d			
	Crustacea toxicity	NOEC	51 mg/l	21 d	Daphnia magna	Review article or handbook (2009)	OECD Guideline 211
	Acute bacteria toxicity	(EC50 mg/l)	1385	3 h	activated sludge, domestic	Study report (1989)	OECD Guideline 209
2855-13-2	3-aminomethyl-3,5,5-trime	ethylcyclohe	xylamine				
	Acute fish toxicity	LC50	110 mg/l	96 h	Leuciscus idus	REACh Registration Dossier	EU Method C.1
	Acute algae toxicity	ErC50	37 mg/l	72 h	Desmodesmus subspicatus	REACh Registration Dossier	EU Method C.3
	Acute crustacea toxicity	EC50	23 mg/l	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202
	Crustacea toxicity	NOEC	3 mg/l	21 d	Daphnia magna	REACh Registration Dossier	other: OECD 202, part 2
15520-10-2	2-methylpentane-1,5-dian	nine					
	Acute fish toxicity	LC50 mg/l	1825	96 h	Pimephales promelas	REACh Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Raphidocelis subcapitata	REACh Registration Dossier	EU Method C.3
	Acute crustacea toxicity	EC50 mg/l	23,4	48 h	Daphnia magna	Study report (1985)	OECD Guideline 202
	Crustacea toxicity	NOEC mg/l	>= 9,3	21 d	Daphnia magna	REACh Registration Dossier	EU Method C.20



according to Regulation (EC) No 1907/2006

ARC 791(E) Part B					
Revision date: 10.07.2023				Page 13 of 17	
Acute bacteria toxicity	(EC50 1558 mg/l)	3 h	REACh Registration Dossier		

#### 12.2. Persistence and degradability

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
100-51-6	benzyl alcohol				
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A 95 - 97% 21				
	Readily biodegradable (according to OECD criteria).				
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A 8 % 28				
	Not readily biodegradable (according to OECD criteria)				

#### 12.3. Bioaccumulative potential

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-51-6	benzyl alcohol	1
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	0,99
15520-10-2	2-methylpentane-1,5-diamine	0

## BCF

CAS No	Chemical name	BCF	Species	Source
100-51-6	benzyl alcohol	1,371	QSAR model	http://epa.gov/oppt/
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexy lamine	2,63		REACh Registration D

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No information available.

## **Further information**

Do not allow to enter into surface water or drains.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 14 of 17

#### **Disposal recommendations**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. The waste code has to be identified in agreement with the disposal company or the competent authority.

#### Contaminated packaging

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine,

2-methylpentane-1,5-diamine)

14.3. Transport hazard class(es): Ш 14.4. Packing group: Hazard label: 8 Classification code: C7 Special Provisions: 274 Limited quantity: 5 L Excepted quantity: E1 Transport category: 3 Hazard No: 80 Tunnel restriction code: Ε

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine,

2-methylpentane-1,5-diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Classification code:C7Special Provisions:274Limited quantity:5 LExcepted quantity:E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine,

2-methylpentane-1,5-diamine)

 14.3. Transport hazard class(es):
 8

 14.4. Packing group:
 III

 Hazard label:
 8

 Special Provisions:
 223 274

 Limited quantity:
 5 L



according to Regulation (EC) No 1907/2006

ARC 791(E) Part B

Revision date: 10.07.2023 Page 15 of 17

Excepted quantity: E1
EmS: F-A, S-B
Segregation group: 18 - alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2735

**14.2. UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine,

2-methylpentane-1,5-diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:1 I

Limited quantity Passenger: 1 L
Passenger LQ: Y841
Excepted quantity: E1

IATA-packing instructions - Passenger:852IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:856IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

## 14.7. Maritime transport in bulk according to IMO instruments

No information available.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): < 500 g/l (A&B)

Subcategory according to Directive Two-pack reactive performance coatings for specific end use such as

2004/42/EC: floors - Solvent-borne coatings, VOC limit value: 500 g/l

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

## 15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 16 of 17

2-methylpentane-1,5-diamine

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,5,7,8,9,11,12,14,15.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID:Règlement international conernat le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effectice concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Corr. 1; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method

### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.



according to Regulation (EC) No 1907/2006

## ARC 791(E) Part B

Revision date: 10.07.2023 Page 17 of 17

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)