

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

740(E) Heavy Duty Rust Guard (Aerosol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coats and protects metal like a paint with minimum surface preparation but is easily removable. Heavy Duty Rust Guard can be used for the protection of metal, tools, fixtures, parts-in-process, equipment, tanks, structures, machinery, tubing, castings, rod, bar and sheet stock. Effective to 80°C (175°F).

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	D-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229
Asp. Tox. 1; H304
STOT SE 3; H336
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 2 of 17

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 3 of 17

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics			70 - < 75 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
106-97-8	butane			7-13 %
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			
74-98-6	propane			7-13 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1; H220			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			5 - < 10 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
110-82-7	cyclohexane			< 1 %
	203-806-2	601-017-00-1	01-2119463273-41	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-48-9	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics	70 - < 75 %
	inhalation: LC50 = > 4,96 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
106-97-8	203-448-7	butane	7-13 %
	inhalation: LC50 = 273000 ppm (gases)		
	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	5 - < 10 %
	inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg		
110-82-7	203-806-2	cyclohexane	< 1 %
	inhalation: LC50 = > 5540 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg Aquatic Acute 1; H400: M=1		

Further Information

No information available.

SECTION 4: First aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 4 of 17

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

Remove person to fresh air and keep comfortable for breathing.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let 1 glass of water be drunken in little sips (dilution effect).

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Causes eye irritation. Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Most important symptoms and effects, both acute and delayed: Headache, Dizziness, Pulmonary oedema
Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- alcohol resistant foam
- Water spray jet
- Carbon dioxide (CO₂)
- Dry extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting.
Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings.
In case of fire: Wear self-contained breathing apparatus.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 5 of 17

Special protective equipment for firefighters: Protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Safe handling: see section 7

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Personal protection equipment: see section 8

Advice on protection against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothes. Use protective skin cream before handling the product. Remove contaminated, saturated clothing immediately. When using do not eat, drink, smoke, sniff. Wash hands and face before breaks and after work and take a shower if necessary.

Further information on handling

Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 6 of 17

Requirements for storage rooms and vessels

Keep cool. Protect from sunlight.
Pressurised container: May burst if heated.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Keep away from:

- Frost
- Heat
- Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
74-98-6	Aliphatic hydrocarbon gases, Alkanes (C1-C3), Propane	-	-		Asphyxiant	
106-97-8	Butane, all isomers - n-butane	1000	-		STEL (15 min)	
110-82-7	Cyclohexane	200	700		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 7 of 17

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics			
Worker DNEL, long-term		inhalation	systemic	871 mg/m ³
Worker DNEL, long-term		dermal	systemic	77 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m ³
Consumer DNEL, long-term		dermal	systemic	46 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	46 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	1286,4 mg/m ³
Worker DNEL, long-term		inhalation	local	837,5 mg/m ³
Worker DNEL, acute		inhalation	local	1066,67 mg/m ³
Consumer DNEL, acute		inhalation	systemic	1152 mg/m ³
Consumer DNEL, long-term		inhalation	local	178,57 mg/m ³
Consumer DNEL, acute		inhalation	local	640 mg/m ³
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
110-82-7	cyclohexane			
Worker DNEL, long-term		inhalation	systemic	700 mg/m ³
Worker DNEL, acute		inhalation	systemic	1400 mg/m ³
Worker DNEL, long-term		inhalation	local	700 mg/m ³
Worker DNEL, acute		inhalation	local	1400 mg/m ³
Worker DNEL, long-term		dermal	systemic	2016 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	206 mg/m ³
Consumer DNEL, acute		inhalation	systemic	412 mg/m ³
Consumer DNEL, long-term		inhalation	local	206 mg/m ³
Consumer DNEL, acute		inhalation	local	412 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1186 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	59,4 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 8 of 17

PNEC values

CAS No	Substance	
Environmental compartment		Value
110-82-7	cyclohexane	
Freshwater		0,0447 mg/l
Freshwater (intermittent releases)		0,009 mg/l
Marine water		0,00447 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		0,36 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,24 mg/l
Soil		0,694 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

- Eye glasses with side protection
- goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374

NBR (Nitrile rubber),

Wearing time with permanent contact: Thickness of the glove material: $\geq 0,4$ mm, Breakthrough time: >480 min

Wearing time with occasional contact (splashes): Thickness of the glove material: $\geq 0,1$ mm, Breakthrough time: > 30 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

Skin protection

Protective clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Filtering device (full mask or mouthpiece) with filter: AX

Thermal hazards

No data available

Environmental exposure controls

No special measures are necessary.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 9 of 17

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Mineral oil	
		Test method
Melting point/freezing point:	No data available	
Boiling point or initial boiling point and boiling range:	98 °C	
Flammability		
Solid/liquid:	No data available	
Gas:	No data available	
Lower explosion limits:	1,1 g/m ³	
Upper explosion limits:	9,0 g/m ³	
Flash point:	-8 °C	
Auto-ignition temperature:	No data available	
Decomposition temperature:	No data available	
pH-Value:	No data available	
Water solubility:	Immiscible	
Solubility in other solvents		
No information available.		
Partition coefficient n-octanol/water:	No data available	
Vapour pressure:	No data available	
Density (at 20 °C):	0,79 g/cm ³	
Relative vapour density:	>1 (air = 1)	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
Vapours can form explosive mixtures with air.	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	No data available
Gas:	No data available
Oxidizing properties	
No information available.	

Other safety characteristics

Evaporation rate:	<1 (Ether = 1)
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
Viscosity / dynamic:	No data available

Further Information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 10 of 17

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

This material is considered to be non-reactive under normal use conditions.

10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

10.5. Incompatible materials

- Oxidising agent, strong

10.6. Hazardous decomposition products

- Nitrogen oxides (NO_x),
- Carbon dioxide (CO₂),
- Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 11 of 17

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 4,96 mg/l	Rat	Study report (1992)	OECD Guideline 403
106-97-8	butane				
	inhalation (4 h) gas	LC50 273000 ppm	Rat	GESTIS	
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat	Study report (1988)	Group of rats were exposed to test subst
110-82-7	cyclohexane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 5540 mg/l	Rat	Study report (1981)	OECD Guideline 403

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 12 of 17

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 13 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Danio rerio	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 > 100 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Fish toxicity	NOEC 0,131 mg/l	28 d	Oncorhynchus mykiss	Company report (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC > 10,2 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
106-97-8	butane					
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 19,37 mg/l	96 h		USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
74-98-6	propane					
	Acute fish toxicity	LC50 49,9 mg/l	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute algae toxicity	ErC50 10 - 30 mg/l	72 h	Raphidocelis subcapitata	Study report (1995)	OECD Guideline 201
	Fish toxicity	NOEC 2,045 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 14 of 17

	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
110-82-7	cyclohexane						
	Acute fish toxicity	LC50 mg/l	4,53	96 h	Pimephales promelas	Vol. 5, Centre for Lake Superior Studies	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	9,317	72 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50	0,9 mg/l	48 h	Daphnia magna	Publication (1987)	OECD Guideline 202

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics	>= 3,17
106-97-8	butane	1,09
74-98-6	propane	1,09
110-82-7	cyclohexane	3,44

BCF

CAS No	Chemical name	BCF	Species	Source
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics	>= 30,85	calculated	REACH Registration D
110-82-7	cyclohexane	167	Pimephales promelas	J. Fish. Board Can.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 15 of 17

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2.1
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Special Provisions:	63, 190, 277, 327, 344, 381, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS, FLAMMABLE
<u>14.3. Transport hazard class(es):</u>	2.1
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 16 of 17

Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 57

2010/75/EU (VOC): 710 g/l
Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics

butane

propane

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

cyclohexane

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 4,5,6,7,8,10,11,12,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

740(E) Heavy Duty Rust Guard (Aerosol)

Revision date: 03.01.2023

Page 17 of 17

IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 EC50: Effectice concentration, 50 percent
 DNEL: Derived No Effect Level
 PNEC: Predicted No Effect Concentration
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)